

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A45D 19/02, 24/26, B65D 35/36</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/26510</p> <p>(43) International Publication Date: 3 June 1999 (03.06.99)</p>
<p>(21) International Application Number: PCT/US98/24835</p> <p>(22) International Filing Date: 20 November 1998 (20.11.98)</p> <p>(30) Priority Data: 9724714.2 21 November 1997 (21.11.97) GB</p> <p>(71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): BURROWES, Lee [GB/GB]; 27 St. Marys Road, Horsell, Woking TW20 9NW (GB). ALLEN, Lesley [GB/GB]; Monks Cottage, Medmenham, Nr. Marlow, Bucks SL7 2EZ (GB).</p> <p>(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).</p>		<p>(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>

(54) Title: FLUID APPLICATORS

(57) Abstract

An applicator system, for use in delivering a flowable composition, wherein a container (10) in which the flowable composition is to be contained; and at least three applicators (114, 106, 72) of different type, each of the applicators having at least one outlet (148, 108, 88) through which the flowable composition is to be applied, with at least a first of the applicators (72) being securable to the container, and with at least a second of the applicators (114, 106) being securable to the first of the applicators; wherein only at least one outlet of a selected one of the at least three applicators is exposed at any one time while applying the flowable composition therethrough.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPLICATORS

The present invention relates generally to applicators and more especially but not exclusively to applicators for use in applying hair and/or scalp compositions to the hair and/or scalp in a time-efficient, controlled and mess-free manner.

In a hair colouring treatment, it would be desirable to be able to control flow of a colouring fluid accurately and to be able to target the areas to be coloured by the colouring fluid precisely. It would also be desirable to be able to minimise mess during application and manipulation, and to be able to achieve an even colour distribution throughout the areas to be coloured by the colouring fluid.

These objectives are to be achievable even when the applicator is to be handled by the person to whom the colouring fluid is to be applied.

Different aspects of the present invention which address these objectives, and similar objectives in situations using other flowable compositions, will now be discussed, in turn, with preferred applicators embodying more than one or all of the different aspects of the present invention.

A. It is known from US-A-4209027 for a hair treatment device to be securable to a squeeze bottle containing a hair treating liquid which is to be dispensed by a user through discharge orifices in different applicators simultaneously presented by the hair treatment device.

One of the applicators has an elongate tip for use primarily as parting means, and others of the applicators

are alternative brushes and combs for use primarily as spreading means, with a valve being provided for enabling the hair treating liquid to be directed to the parting means or the spreading means or both.

A practical disadvantage of this known hair treatment device is that it can be awkward to handle in a controlled and mess-free manner.

The result of this is that, when using one of the spreading means, hair which is not to be treated or has already been treated may be locally damaged or discoloured by undesired contact with hair treating liquid in and around the discharge orifice of the parting means, and furthermore hair treating liquid may drip or be flicked from the parting means onto the user's skin, clothes or surroundings.

According to a first aspect of the present invention, however, an applicator system for use in delivering a flowable composition comprises:-

a container in which the flowable composition is to be contained; and

at least three applicators of different type, each of the applicators having at least one outlet through which the flowable composition is to be applied, with at least a first of the applicators being securable to the container, and with at least a second of the applicators being securable to the first of the applicators;

characterised in that only the at least one outlet of a selected one of the at least three applicators is exposed at any one time while applying the flowable composition therethrough.

The fact that only the at least one outlet of the selected applicator is exposed, during use, means that manipulation of the selected applicator does not involve any risk of mess by any flowable composition left in or on the other applicators.

B. Many hair treatment devices have an applicator in the form of an elongate dispensing spout which gradually narrows along its length to a free end provided with a discharge orifice.

As disclosed in JP(UM)-A-7-22951, such a hair treatment device can also have an applicator in the form of a comb provided with an internal passage for directing a hair composition from the discharge orifice of the spout to a plurality of small holes in teeth of the comb.

In use, the comb is a push fit over the spout such that the comb extends beyond the free end of the spout and is retained along part of the length of the spout by friction.

It has been found, in practice, that if movement of the comb is impeded by any knots or tangles in the hair, the bending moment and torque at the junction of the comb with the spout can be such that the comb is simultaneously pulled off the spout and rotated about the spout.

A similar structure is disclosed in JP-A-9-118375, which discloses how two liquids can be mixed and then delivered through a comb which is detachably securable to a nozzle by any appropriate means. The two liquids may form a hair colouring composition. However, spillage of hair colouring composition down the outside of the nozzle could result in failure to be able to attach the comb to

the nozzle. This is because the hair colouring composition would act as a lubricant and would deleteriously affect any snap and/or threaded fit of the comb to the nozzle.

According to a second aspect of the present invention, however, an applicator system for use in delivering a flowable composition comprises:-

a container in which the flowable composition is to be contained;

first applicator means having first outlet means, the first applicator means being attachable to the container in a manner such that the flowable composition in the container can be dispensed through the first outlet means; and

second applicator means having second outlet means, the second applicator means being locatable over the first applicator means in a manner such that the flowable composition can pass through the first outlet means before being dispensed through the second outlet means;

characterised in that the second applicator means is attachable to the container.

The fact that the second applicator means is attached to the container, during use, rather than being attached to the first applicator means, can result in a stronger construction in which the second applicator means is far less likely to rotate or come apart.

C,D. Hair treatment devices are typically provided with different types of applicator to suit different hair treatment situations.

For example, there can be advantages in having a dispensing spout to allow a line of hair composition to be applied, a dispensing pervious member such as a cloth to allow hair composition to be wiped over the hair, and a dispensing comb or brush to allow hair composition to be thoroughly worked throughout the length of the hair.

Indeed US-A-4211247 discloses such dispensing applicators and also discloses non-dispensing sponges for use in merely spreading hair composition after the hair composition has been applied by a dispensing applicator.

According to a third aspect of the present invention, however, an applicator system for use in delivering a flowable composition comprises:-

a container in which the flowable composition is to be contained; and

at least three applicators of different type, including a line applicator in which the flowable composition is delivered through a single outlet, a surface applicator in which the flowable composition is delivered through a plurality of outlets onto a surface, and a brush/comb-like applicator in which the flowable composition is delivered through a plurality of outlets and dispersed by a plurality of elongate parting members;

characterised in that the surface applicator is of foam or sponge material having a resiliently compressible porous structure from which the flowable composition is to be delivered.

The fact that the surface applicator is in the form of a resiliently compressible foam or sponge means that,

during use, there can be a much more even application of the flowable composition than had hitherto been possible just by wiping with a cloth because the foam or sponge can absorb and redistribute the flowable composition.

According to a fourth aspect of the present invention, moreover, an applicator system for use in delivering a flowable composition comprises:-

a container in which the flowable composition is to be contained; and

at least three applicators of different type, including a line applicator in which the flowable composition is delivered through a single outlet, a surface applicator in which the flowable composition is delivered through a plurality of outlets onto a surface, and a brush/comb-like applicator in which the flowable composition is delivered through a plurality of outlets and dispersed by a plurality of elongate parting members;

characterised in that at least two of the plurality of outlets in the brush/comb-like applicator are formed in respective ones of the elongate parting members.

The fact that at least two of the elongate parting members have their own outlets means that, during use, the elongate parting members are better able to disperse the flowable composition, which is particularly important when the flowable composition is a hair colouring composition.

In a particularly preferred embodiment of an applicator system, embodying all four of the above-noted different aspects of the present invention:-

(a) one of the applicators is a spout having a single

elongate passageway through which the flowable composition is to be dispensed,

(b) another of the applicators is of foam or sponge material having a resiliently compressible porous structure from which the flowable composition is to be delivered, and

(c) yet another of the applicators has a plurality of elongate parting members projecting from a support to which the flowable composition is delivered through a housing.

Preferably, the foam or sponge material is in the form of a pad at or near one end of a carrier. For ease of assembly, the carrier may be a detachable push fit on the spout. For ease of application, particularly when targeting specific areas, the pad may extend only partly around the circumference of the carrier.

Preferably, each of the elongate parting members is in the form of a substantially rigid tooth. For ease of manufacture, particularly when moulding in a plastics material, the teeth may be arranged in at least one row. The teeth may but need not necessarily have generally triangular outlines of different transverse dimensions when viewed from an end of the at least one row. For ease of subsequent dispersal, the flowable composition may be delivered from the teeth and, for example, a free end of each of the teeth may have at least one of the outlets.

Preferably, the elongate parting members and the support are removably detachable from the housing. This allows the provision of a plurality of the supports, from which one is to be selected by a user, the elongate parting members of different supports being of different type. For example, a comb-like support with substantially

rigid teeth may be replaced by a brush-like support with flexible filaments.

Preferably, the elongate parting members and the support are formed as a unit which is securable to the housing by securing means including a catch. The catch may be resiliently deflectable and engageable with an aperture extending through the housing such that the catch is releasable remotely from the elongate parting members.

There may be a further catch operable as a pivot. The resiliently deflectable catch should be releasable by finger pressure - it may, however, be possible for the elongate parting members and the support to be removed from the housing merely by rolling the housing over a hard surface, thereby releasing the resiliently deflectable catch.

For ease and strength of assembly, the housing may be a removable screw fit with the container, both the housing and the container being formed with lug means which snap passed one another when the housing has been fully screwed onto the container, at a predetermined alignment.

The spout may be a push fit with the container.

To facilitate delivery of the flowable composition, when the flowable composition passes through an applicator in the form of a spout before being dispensed through an applicator in the form of a housing and a support with a plurality of elongate parting members projecting from the support, the housing may have a guide tube which receives a free end of the spout when the housing is located over the spout.

Preferably, the container is a bag-in-bottle container such that the flowable composition can be

delivered at any orientation of the bag-in-bottle container.

In such containers, an inner collapsible layer defines a reservoir, and an outer deformable layer is separated from the inner collapsible layer by a buffer zone. Valve means is operable to control entry of air into the buffer zone (bottle) and exit of flowable composition from the reservoir (bag). In order to simplify assembly, with consequent commercial advantages, the valve means may comprise a valve member of unitary construction.

Indeed, the valve member may comprise an annular flapper valve for controlling the opening of one or more air inlets in the spout, the annular flapper valve surrounding a central quadrolobe valve for controlling the opening of the single elongate passageway in the spout, and the central quadrolobe valve being a push fit within the single elongate passageway in the spout.

It will be appreciated that the flowable composition may be a hair and/or scalp composition.

An applicator system, according to the present invention, will now be described in greater detail, by way of example only, with reference to the accompanying drawings, wherein:-

Figure 1 is an exploded perspective view of a cap, a bottle, a flexible bag, a support tube, an insert, a valve, a spout, a sponge pad, a comb housing and a comb - all being components in a hair colouring kit embodying the present invention;

Figure 2 is a fragmentary enlarged cross-sectional

view showing the cap when secured to the bottle;

Figure 3 is a plan view of the insert;

Figure 4 is a schematic cross-sectional view, taken perpendicularly to the cross-sectional view of Figure 2, showing a dye container when docked with the insert to allow dye in the dye container to be added to the flexible bag;

Figure 5 is a perspective view showing the spout when secured to the bottle;

Figure 6 is a fragmentary enlarged cross-sectional view of Figure 5;

Figure 7 is a perspective view similar to Figure 5 but showing the sponge pad when secured to the spout;

Figure 8 is a cross-sectional view of Figure 7;

Figure 9 is a perspective view showing the comb housing when secured to the bottle with the comb secured to the comb housing;

Figure 10 is a cross-sectional view of Figure 9; and

Figures 11 and 12 are, respectively, cross-sectional views of the comb and the comb housing before being secured together.

The accompanying drawings illustrate a hair colouring kit embodying all aspects of the present invention - the different inventive aspects, for which protection is being sought in the present and several contemporaneous patent applications, relate to a delivery system as well as to

various applicators and applicator systems for use in delivering a flowable composition.

Although the flowable composition is preferably a hair colouring composition, no aspect of the present invention is restricted to such a specific flowable composition. Other examples of flowable compositions are: medicaments e.g. for petcare; foodstuffs e.g. cake mixes; cleaning fluids e.g. for garmentcare or carpetcare; cosmetics e.g. body lotions or moisturisers; adhesives or lubricants.

Use of a hair colouring composition can be problematical.

One problem is that the hair colouring composition may need to be prepared from two or more component materials just prior to use. This means that the component materials need to be stored separately in a manner allowing a user to mix the component materials when required. Typically, one of the component materials is hydrogen peroxide and another of the component materials is a dye. The user must not, however, be exposed to any danger or any risk of staining when adding the dye to the hydrogen peroxide.

Another problem is that the hair colouring composition may need to be applied to the hair through an applicator at any angle. If the applicator is fed from a simple squeeze bottle, the applicator will be ready for use in any orientation when the squeeze bottle is full. However, as the squeeze bottle is progressively emptied, it is found that the applicator is not ready for immediate use in any orientation, but may first need to be primed to offset the effect of any suckback of the hair colouring composition. This makes it difficult to control the

application of the hair colouring composition, particularly to the hairline whilst avoiding staining of the skin.

The present hair colouring kit not only allows the hair colouring composition to be prepared just prior to use, but has applicators fed by a user-controlled delivery system in which the hair colouring composition is discharged by a mechanically generated pressure differential (not an aerosol) in such a way that the hair colouring composition is always ready to be discharged at any orientation of the delivery system.

All orientation delivery is possible for all of the hair colouring composition which is discharged - which can be over 90% or even 95% of the hair colouring composition which has been prepared.

The present hair colouring kit also allows the hair colouring composition to be delivered in user-regulated amounts through applicators to specific areas to achieve an even colour distribution with minimal mess.

No one applicator is equally suitable, even if carefully manipulated, for applying hair colouring composition to the roots, the hairline and the main body of a head of hair. It is therefore usual to provide applicators of different types selected from a line applicator, a surface applicator and a brush/comb-like applicator. The line applicator can be a spout with a single outlet and the surface applicator can be of porous material with a plurality of outlets. The brush/comb-like applicator can have a plurality of outlets for dispensing hair colouring composition which is then dispersed by a plurality of elongate parting members. As might be expected, the elongate parting members might resemble the

bristles of a brush or the teeth of a comb. All of the different applicator types are to be brought into fluid communication with a container for the hair colouring composition.

Specific advantages of the present hair colouring kit are that:-

- (a) only a selected one of three applicators of different type is exposed during use so that there is no risk during manipulation of the hair of mess being caused by any hair colouring composition left in or on the other applicators;
- (b) a surface applicator from three applicators of different type is of foam or sponge material having a resiliently compressible porous structure to provide improved spreading of the hair colouring composition; and
- (c) a brush/comb-like applicator from three applicators of different type has at least two of its outlets formed in respective ones of its elongate parting members to provide improved dispersal of the hair colouring composition.

Other specific advantages of the present hair colouring kit are that a one-piece valve simultaneously performs the dual functions of controlling entry of air and exit of hair colouring composition, a support for elongate parting members is secured to a housing by at least one catch which is releasable from a position remote from the hair colouring composition and, with a line applicator attached to a container, a brush/comb-like applicator is locatable over the line applicator yet is still attachable directly to the container.

Before describing a surface applicator with reference to Figures 7 and 8, and a brush/comb-like applicator with reference to Figures 9 to 12, a delivery system incorporating a line applicator will be described with reference to Figures 1 to 6.

A bottle 10 may be formed with a hollow body 12 which is of generally oval section and is closed at a lower end but has an open neck 14 at an upper end. The neck may be formed with an external thread 16. The neck 14 may also be formed with a pair of opposed lug means 18 of which only one is shown in Figure 1. Each of the lug means 18 preferably includes a gap 20 approached by a ramp 22 for a purpose to be described hereinafter.

At least the body 12 may be formed of a resiliently deformable plastics material such that the bottle 10 can quickly reform in shape when released from having been squeezed. The plastics material may be low density polyethylene, linear low density polyethylene (LLDPE) or polypropylene and may be transparent. If not transparent, the plastics material is preferably translucent and may or may not be coloured.

A flexible bag 24 may be formed of two overlapping sheets 26 of the same shape which are sealed together around most of their common periphery to form a side sealed sachet having an upper opening 28 and a lower V-shaped edge 30. The bag 24 defines a reservoir for a first material, such as hydrogen peroxide, and should therefore provide a good moisture barrier. Each of the sheets 26 may be of laminated metallised material, and preferably includes the following three layers: LLDPE sealant/adhesive/metallised PET (polyethylterphalate).

The bag 24 is insertable into the bottle 10 through the neck 14 to form a container with an outer deformable layer (body 12) and an inner collapsible layer (sheets 26) separated from one another by a buffer zone 32, as shown in Figure 4.

As also shown in Figure 4, a support tube 34 may be insertable into the bag 24 through the opening 28. The tube 34 may have a plurality of holes 36 along its length and provide an at least partially rigid channel which is open in cross-section. A lower end 38 of the tube 34 may be open or closed. The lower end 38 of the tube 34 can be in contact with the bag 24 - alternatively, the lower end 38 of the tube 34 may be close to but not in contact with the V-shaped edge 30 of the bag 24. An upper end of the tube 34 may be secured to an insert 40 by any suitable method or means, and may be a simple push fit in the insert 40.

The insert 40 is partially insertable into the bag 24 through the opening 28 and is also partially insertable into the bottle 10 through the neck 14. Preferably, the insert is permanently fixed in a fluid tight manner to the sheets 26 around the opening 28, for example by heat or ultrasonic welding. The insert 40 and the bag 24 could alternatively be of unitary construction. The insert 40 is preferably irremovably fixed to the neck 14 by a simple push fit or any other suitable method or means but could alternatively be removable by a user to achieve a refillable system.

As shown in Figures 2, 4 and 6, the insert 40 may be a one-piece plastics moulding having a tubular member 42 which defines an orifice and extends centrally of a side wall 44, a transverse wall 46 and a pair of opposed lower sections 48.

The side wall 44 is shown with an outwardly extending flange 50 at its upper end, for limiting insertion of the insert 40 into the bottle 10, and an inwardly directed rib 52 at a position generally mid-way between the flange 50 and the transverse wall 46. The transverse wall 46 is shown with a plurality of holes 54 therethrough for joining the buffer zone 32 to an annular channel 56 defined between the tubular member 42 and the side wall 44 and thus surrounding the tubular member 42. The opposed lower sections 48 are shown as hollow, to prevent sinkage in moulding, and thereby facilitate the fluid tight fixing of the insert 40 to the bag 24.

A lower end of the tubular member 42 may be inwardly recessed for receiving the upper end of the tube 34 and an upper end of the tubular member 42 may be inwardly chamfered.

Typically the bag 24 will be supplied to a user when already partially filled with a first material, such as hydrogen peroxide. It will therefore be necessary to prevent the first material escaping through the tube 34 and the tubular member 42. A removable flip top cap could be provided for closing the upper end of the tubular member 42. Alternatively, the upper end of the tubular member 42 could be closed by a rupturable film seal. Preferably, however, a removable cap 58 is provided, as shown in Figure 2.

The cap 58, which may again be a one-piece plastics moulding, may have a plug seal 60 for sealingly closing the upper end of the tubular member 42. A securing part 62 of the cap 58 could be an airtight fit with the neck 14 of the bottle 10. However, there are advantages in forming the securing part 62 of the cap 58 as a non-

airtight fit. For example, there could be an internal thread 64 which is a breathable screw fit with the external thread 16 on the neck 14 of the bottle 10 to provide an air passageway to atmosphere from the annular channel 56.

One advantage is that, if hydrogen peroxide in the bag 24 became unstable and produced oxygen, the bag 24 could expand with air in the buffer zone 32 escaping through the holes 54 in the insert 40 and then between the threads 16 and 64.

Another advantage is that, if the buffer zone 32 were to be subjected to an unwanted pressure change, for example as a result of air travel, air could again either escape from or enter the buffer zone 32 by the above-indicated route.

The hair colouring kit as so far described allows a user to prepare a hair colouring composition or other flowable composition just prior to use.

In practice, at least a second material is added to the first material in the reservoir. If the reservoir had been supplied in an empty state, or had been emptied in a previous use, it would of course first be necessary to add some first material to the reservoir. In any event, the initially separated materials need to be allowed to mix.

As shown schematically, in Figure 4, the second material may be stored in an entirely independent container 66. If the first material is hydrogen peroxide, the second material is likely to be a dye. As dyes can be oxygen sensitive, the container 66 may need to provide an excellent oxygen barrier. Moreover, if the dye is in the form of a gel, cream or paste, for example, the container

66 could need to be plastically deformable to allow a user to squeeze the dye therefrom. On the other hand, if the dye is in the form of a liquid, the dye might be able to exit the container 66 under the influence of gravity.

If the container 66 is resiliently deformable, the bag 24 is preferably inflated with air above the first material - if the container 66 is not resiliently deformable, the bag 24 is preferably deflated.

The user may be supplied with a plurality of the containers 66 and each of the containers 66 may contain a different material such as a different shade of hair colorant with the intention that one or more of the containers 66 are to be emptied into the reservoir to form a particular flowable composition such as a hair colouring composition of specifically selected shade.

It is desirable for the container 66, or each of the containers 66, to include a long nozzle 68 which can extend completely through the tubular member 42 into the tube 34. This can give good docking in that the container 66 is less likely to come apart from the bottle 10 even when the user is using both hands to squeeze the container 66. It can also promote good mixing in that the contents of the container 66 might be squirted from close range directly into the contents of the bag 24. Clearly, it will be necessary for the container 66 to be opened before insertion of the long nozzle 68 into the tubular member 42, and opening may be effected by breaking off, cutting off or twisting off the nozzle's tip 70 (shown in broken outline in Figure 4).

It will be appreciated that, as the second material is emptied from the container 66 into the bag 24, the volume of any air in the bag 24 above the first material

will be progressively reduced, and any such compressed air should be encouraged to escape to prevent the bag 24 from expanding.

If the nozzle 68 is a loose fit in the tubular member 42, the compressed air will escape through that loose fit. Alternatively, one or more splines could be formed along the length of the nozzle 68 and/or one or more air escape castellations could be formed on the dye container adjacent a base of the nozzle 68. Dependent on the nature of the second material in the container 66, and the dimensions, the compressed air might inject upwards through the second material to form an air pocket in the container 66 which expands as the air pocket in the bag 24 contracts.

Even if the bag 24 does expand, air in the buffer zone 32 would escape through the holes 54 in the transverse wall 46 of the insert 40, as previously described.

After sufficient of the second material has been added to the first material, the container 66 is removed from the bottle 10 and is either discarded, or resealed and saved for future use.

As alternatives to adding the second material to the first material by decanting, the second material may be contained in a container which is formed with or located within the bag 24 and which is rupturable, for example by squeezing the body 12 of the bottle 10, or which is otherwise capable of allowing the second material to be added to the first material.

When the second material has been added to the first material, they are preferably mixed at this stage by

shaking the bottle 10. It would be possible for the user to prevent escape of the contents of the bag 24 by placing a gloved finger over the upper end of the tubular member 42 whilst shaking. It may be more convenient, however, for the user to replace the cap 58 so that the plug seal 60 closes the upper end of the tubular member 42. In either case, the tube 34 acts to restrain the bag 24, while shaking and/or inverting the bottle 10, and thereby aids mixing by allowing the contents of the bag 24 to move more freely than the bag 24. It is believed that optimum mixing by shaking occurs if around 10% of the volume of the bag 24 is left as headspace. If the bag 24 and the body 12 of the bottle 10 are both translucent, it is possible to check visually whether or not mixing has been completed.

To prepare for discharge of the flowable composition formed by the first and the second materials, or more specifically the hair colouring composition formed by the hydrogen peroxide and the dye, the insert 40 is again exposed to allow a spout 72 to be attached to the insert 40, as shown in Figures 5 and 6.

The spout 72 may once again be a one-piece plastics moulding, here comprising a cylindrical portion 74 leading to a domed portion 76 which itself leads to a tapered portion 78. A bottom end of the cylindrical portion 74 is formed with an outwardly directed rib 80. A top end of the cylindrical portion 74 is formed adjacent a shoulder 82 presented by the domed portion 76. One or more, such as three, air inlets 84 extend through the domed portion 76 and may be equally circumferentially spaced around the domed portion 76. The tapered portion 78 is formed with an elongate passageway 86 which gradually narrows along its length from a larger lower end to a single outlet 88 at a smaller upper end. An annular recess 90 is formed in

an inner surface of the tapered portion 78 near the larger lower end of the passageway 86. An annular rib 92 is formed on an outer surface of the tapered portion 78 near the smaller upper end of the passageway 86.

A valve member 94, which may be formed of a silicone polymer and may be of unitary construction, is attachable to the spout 72.

Preferably, the valve member 94 includes an inlet part in the form of an annular flapper valve 96 which acts as a one-way check valve to control entry of air through the air inlets 84.

Preferably, the valve member 94 also includes an outlet part in the form of a central quadrolobe valve 98 which acts as a one-way check valve to control exit of hair colouring composition through the passageway 86. A quadrolobe valve 98 is preferred because it opens from the centre not the side and thus gives a smoother flow of hair colouring composition therethrough. However, as alternatives to a quadrolobe valve 98, the outlet part of the valve member 94 could be a flapper valve, an umbrella valve or a duckbill valve.

The flapper valve 96 and the quadrolobe valve 98 may be joined by an intermediate part including a transverse sealing wall 100 and a frusto-conical locating wall 102 whose outer surface has an annular rib 104.

The valve member 94 is easily attached to the spout 72 by pushing the quadrolobe valve 98 into the passageway 86 until the annular rib 104 on the valve member 94 engages with the annular recess 90 in the spout 72.

The spout 72 is then itself easily attached to the

insert 40 by pushing the cylindrical portion 74 of the spout 72 into the annular channel 56 of the insert 40 until the rib 80 on the cylindrical portion 74 snaps passed the rib 52 on the insert 40, with an audible or at least tangible click, at which time the shoulder 82 of the spout 72 is brought into abutment with the flange 50 of the insert 40 and the sealing wall 100 of the valve member 94 is brought into sealing engagement with the upper end of the tubular member 42 of the insert 40.

In an alternative construction, the spout 72 can be attached to the insert 40 by a screw fit rather than the above-noted push fit.

The bottle 10 could be shaken after the spout 72 has been attached to the insert 40 in order to mix or re-mix the flowable composition.

In order to deliver the hair colouring composition from the bag 24 to the outlet 88 in the spout 72, from where the hair colouring composition is discharged in a line to for example the roots of a head of hair, the body 12 of the bottle 10 is squeezed by the user. This compresses the air in the buffer zone 32 but the compressed air cannot escape through the fluid passageway including the holes 54, the annular channel 56 and the air inlets 84 because the flapper valve 96 acts to close the air inlets 84. Instead, the compressed air acts to partly collapse the bag 24 so that some hair colouring composition is forced out through the fluid passageway including the tube 34, the tubular member 42, the frusto-conical locating wall 102 and the quadrolobe valve 98, which opens to let the hair colouring composition therethrough. When the user stops squeezing the body 12 of the bottle 10, the bottle 10 quickly reforms in shape so that the buffer zone 32 expands. The quadrolobe valve

98 closes to prevent suckback of the hair colouring composition beyond the quadrolobe valve 98 and the bag 24 maintains its partly collapsed state. Instead, air is sucked into the buffer zone 32 past the flapper valve 96 which opens to let air in through the air inlets 84.

Squeezing of the body 12 of the bottle 10 is repeated by the user with whatever pressure and frequency is deemed appropriate to the circumstances.

It will be appreciated that the holes 36 in the tube 34 can prevent the hair colouring composition becoming trapped, as the bag 24 is progressively collapsed to bring the sheets 26 of the bag 24 into contact with one another, and the tube 34 might itself collapse to allow flowable composition in the tube 34 to be discharged.

As the hair colouring composition is dispensed, the user may see through the at least translucent body 12 that the bag 24 is collapsing. This should reassure a user who feared that the hair colouring composition could run out without warning.

Although the reservoir for the first material may be a side sealed sachet, as hereinbefore described, the reservoir could take other forms - for example, an inner collapsible layer distinct from an outer deformable layer would also be provided by an inverting-half-bag bottle or a delaminating bottle, the latter preferably peeling progressively away from a neck thereof, or by a compression blown bag integrally moulded with the insert.

Moreover, although the valve member may be of unitary construction but dual function, as hereinbefore described, the valve member could take other forms - for example, separate valves could be provided for controlling exit of

hair colouring composition and entry of air, the latter possibly being a simple air hole in the body of the bottle which a user closes with a finger.

Referring now to Figures 7 and 8, a surface applicator 106 is shown removably secured over the outlet 88 of the spout 72. More particularly, the surface applicator 106 may include a pad 108 of foam or sponge material having a resiliently compressible porous structure. Such a structure not only has a plurality of outlets, but allows hair colouring composition emerging from the outlet 88 to pass through the pad 108 and by careful manipulation be evenly spread along the hairline.

The pad 108 may be located at or near an upper end of a carrier 110 with a lower half of the carrier 110 being frusto-conical in the direction leading from a smaller upper end to a larger lower end. An inner surface of the lower half of the carrier 110 may be formed with an annular recess 112 for detachably engaging with the annular rib 92 on the spout 72 when the carrier 110 is pushed onto the spout 72. The carrier 110 and the spout 72 may be mutually configured to avoid relative rotation.

The pad 108 may present a curved face, to facilitate accurate application, with the curved face extending only partly around the circumference of an upper half of the carrier 110. If the pad 108 is formed of a plastics material, and the carrier 110 is also formed of a plastics material, the pad 108 may be fixed to the carrier 110 by use of an adhesive. Clearly, if the original surface applicator 106 is not to be cleaned and re-used, a range of surface applicators 106 could be provided which are either similar if intended to be disposable or different if intended to be interchangeable.

As shown in Figures 9 to 12, a brush/comb-like applicator 114 could be removably secured over the outlet

88 of the spout 72 instead of the surface applicator 106, the brush/comb-like applicator 114 including a housing 116 and a releasable unit 118.

The brush/comb-like applicator 114 could be a screw fit or a snap fit to the neck 14.

The housing 116 is yet another one-piece plastics moulding here defining, considered from the top, an aperture 120, a tapered open chamber 122 having a series of slotted webs 124 on its opposed major side walls, a guide tube 126 ensuring open communication into the chamber 122 from a chamber 128, a slot 130 at an upper end of the chamber 128, an internal thread 132 near a lower end of the chamber 128, and a pair of opposed lug means 134 at the lower end of the chamber 128.

The internal thread 132 is preferably strippable from a mould without screwing.

The housing 116 is a removable screw fit with the bottle 10 by virtue of the internal thread 132 in the chamber 128 engaging the external thread 16 on the neck 14. As the housing 116 is progressively screwed on, the outlet 88 of the spout 72 enters the guide tube 126. Finally, the lug means 134 cam along the ramps 22 of the lug means 18 and then snap into the gaps 20 of the lug means 18. The snap may give an audible or at least tangible click to indicate that the housing 116 has been fully screwed onto the bottle 10. In this final position, with the lug means 18 and 132 interengaged, the chamber 122 opens in the direction of the major axis of the body 12, which it will be recalled is of generally oval section.

The releasable unit 118, which is the final component

of the present hair colouring kit, may again be formed as a one-piece moulding of a plastics material such as polypropylene, with an additive such as silicone to give a low coefficient of friction.

The releasable unit 118 can be at least in part translucent to signal to a user that the flowable composition is about to be delivered.

The unit 118 comprises a support 136 which is generally planar and gradually tapers from a narrower upper end to a wider lower end. The narrower upper end has a resiliently deflectable catch 138 extending therefrom with a barb-like leading end 138a. The wider lower end has a rigid catch 140 extending therefrom with a barb-like leading end 140a. The periphery of the support 136 is formed with a skirt 142 which is of complementary outline to the opening of the chamber 122. A plurality of elongate parting members, such as substantially rigid teeth 144, project from the support 136 in a direction opposed to the resiliently deflectable catch 138, the rigid catch 140 and the skirt 142. A plurality of outlets 146 for the flowable composition can extend through the support 136.

As shown most clearly in Figure 9, the teeth 144 may be arranged in two rows. The teeth 144 may but need not necessarily have generally triangular outlines of different transverse dimensions when viewed from the ends of the two rows. The transverse dimensions of the teeth 144 may progressively increase from the narrower upper end of the support 136 to the wider lower end of the support 136. Moreover, the teeth 144 of the different rows may be staggered with respect to one another, and may again have generally triangular outlines but now of generally similar thicknesses when viewed from the sides of the two rows.

As shown most clearly in Figure 11, at least two but possibly all of the outlets 146 further extend through respective ones of the teeth 144. However, it may be desirable for one or more of the outlets 146 not to extend through the teeth 144. For example, at least one outlet 146 may be positioned in the support 136 between adjacent ones of the teeth 144. At least two but possibly all of the outlets 146 which extend through the teeth 144 may emerge through orifices 148 at the free ends of the teeth 144.

In fact, although it is convenient to state that the orifices 148 are at the free ends of the teeth 144, the orifices 148 may be slightly set back from the free ends of the teeth 144, partly to avoid direct coating of the scalp, and partly as a result of a preferred moulding technique known as the passing face shut off technique, which allows the orifices 148 to be formed by a simple two-part mould without need of side pins.

To assemble the unit 118 with the housing 116, it is merely necessary to locate the barb-like leading end 140a of the rigid catch 140 in the slot 130 and then pivot. This brings the free edge of the skirt 142 into engagement with the slotted webs 124 and also deflects the barb-like leading end 138a of the catch 138 to allow entry of the catch 138 into the aperture 120. The unit 118 is fully secured to the housing 116 when the barb-like leading end 138a of the catch 138 emerges from the aperture 120 to snap engage with the material of the housing 116 around the aperture 120.

To remove the unit 118 from the housing 116, the reverse procedure is followed. The catch 138 is releasable by finger pressure. Alternatively, it may be

possible to release the catch 138 by rolling the housing 116 over a hard surface in a manner such that the hard surface knocks the barb-like leading end 138a of the catch 138 back into the aperture 120. It will be appreciated that release of the catch 138 occurs remotely of the orifices 148.

One reason for removing the unit 118 from the housing 116 may be to facilitate cleaning of any residual hair colouring composition.

Another reason for removing the unit 118 from the housing 116 may be to allow replacement by another unit 118 of different type. For example, it may be desirable to replace the substantially rigid teeth 144, which give a comb-like construction, by either a brush-like construction including a plurality of resiliently flexible bristles, or a sponge-like construction or, indeed, another comb-like construction in which there are teeth and/or orifices of different dimensions and/or different configurations. This may facilitate thorough dispersal of dispensed hair colouring composition in different situations, such as different hair lengths or different hair types.

The dimensions, positions and shapes of the orifices 148 may be changed, in different units 118, dependent on the rheology of the hair colouring composition, or on the need for different colouring results such as root coverage, streaking or highlighting.

As a general matter, relevant to all of the present disclosure, the first container in which the first material is to be held can be construed as including the bottle when fitted with any one or combination of the different applicators.

As another general matter, relevant to all of the present disclosure, the flowable composition can be capable of demonstrating pseudo-plastic flow behaviour, here meaning that the flowable composition decreases in viscosity as it is sheared and, once the shearing has stopped, the internal structure of the flowable composition (which was responsible for the original viscosity) rebuilds very quickly causing an increase in viscosity approaching that of the original viscosity.

The flowable composition should be capable of the above-noted pseudo-plastic flow behaviour within a shear strain rate range of 0.01s^{-1} to $10,000\text{s}^{-1}$, which is the most probable shear strain rate range to be encountered when the flowable composition is a hair colouring composition.

An example of a suitable flowable composition could have a viscosity of no less than $0.01\text{ Pa}\cdot\text{s}$ (preferably no less than $0.15\text{ Pa}\cdot\text{s}$) when measured at a shear strain rate of 2000s^{-1} and no more than $5\text{ Pa}\cdot\text{s}$ (preferably no more than $1.4\text{ Pa}\cdot\text{s}$) when measured at a shear strain rate of 10s^{-1} .

What is claimed is:

1. An applicator system, for use in delivering a flowable composition, comprising:-

a container in which the flowable composition is to be contained; and

at least three applicators of different type, each of the applicators having at least one outlet through which the flowable composition is to be applied, with at least a first of the applicators being securable to the container, and with at least a second of the applicators being securable to the first of the applicators;

characterised in that only the at least one outlet of a selected one of the at least three applicators is exposed at any one time while applying the flowable composition therethrough.

2. An applicator system according to claim 1, wherein the first of the applicators is a spout.

3. An applicator system according to claim 1 or claim 2, wherein a third of the applicators has a plurality of elongate parting members.

4. An applicator system according to any of claims 1 to 3, wherein the second of the applicators is of porous material.

5. An applicator system, for use in delivering a flowable composition, comprising:-

a container in which the flowable composition is to be contained;

first applicator means having first outlet means, the first applicator means being attachable to the container in a manner such that the flowable composition in the container can be dispensed through the first outlet means; and

second applicator means having second outlet means, the second applicator means being locatable over the first applicator means in a manner such that the flowable composition can pass through the first outlet means before being dispensed through the second outlet means;

characterised in that the second applicator means is attachable to the container.

6. An applicator system according to claim 5, wherein the first applicator means is a spout.

7. An applicator system according to claim 5 or claim 6, wherein the second applicator means has a plurality of elongate parting members.

8. An applicator system according to any of claims 5 to 7, wherein third applicator means of porous material is attachable to the first applicator means.

9. An applicator system according to claim 8, wherein only a selected one of the three applicator means is exposed at any one time while applying the flowable composition therethrough.

10. An applicator system, for use in delivering a flowable composition, comprising:-

a container in which the flowable composition is to

be contained; and

at least three applicators of different type, including a line applicator in which the flowable composition is delivered through a single outlet, a surface applicator in which the flowable composition is delivered through a plurality of outlets onto a surface, and a brush/comb-like applicator in which the flowable composition is delivered through a plurality of outlets and dispersed by a plurality of elongate parting members;

characterised in that the surface applicator is of foam or sponge material having a resiliently compressible porous structure from which the flowable composition is to be delivered.

11. An applicator system, for use in delivering a flowable composition, comprising:-

a container in which the flowable composition is to be contained; and

at least three applicators of different type, including a line applicator in which the flowable composition is delivered through a single outlet, a surface applicator in which the flowable composition is delivered through a plurality of outlets onto a surface, and a brush/comb-like applicator in which the flowable composition is delivered through a plurality of outlets and dispersed by a plurality of elongate parting members;

characterised in that at least two of the plurality of outlets in the brush/comb-like applicator are formed in respective ones of the elongate parting members.

12. An applicator system according to claim 11, wherein the surface applicator is of porous material.

13. An applicator system according to any of claims 4, 8, 9 or 12, wherein the porous material is a resiliently compressible foam or sponge material.

14. An applicator system according to claim 10 or claim 13, wherein the foam or sponge material is in the form of a pad at or near one end of a carrier.

15. An applicator system according to claim 2 or claim 7, or any claim when dependent on claim 2 or claim 7, wherein the spout has a single elongate passageway through which the flowable composition is to be dispensed.

16. An applicator system according to claim 10 or claim 11, or any claim when dependent on claim 10 or claim 11, wherein the line applicator is a spout having a single elongate passageway through which the flowable composition is to be dispensed.

17. An applicator system according to claim 14 and claim 15, wherein the carrier is a detachable push fit on the spout.

18. An applicator system according to claim 14 and claim 16, wherein the carrier is a detachable push fit on the spout.

19. An applicator system according to claim 17 or claim 18, wherein the pad extends only partly around the circumference of the carrier.

20. An applicator system according to any of claims 15 to 19, wherein the spout is a push fit with the container.

21. An applicator system according to any of claims 15 to

20, wherein an air inlet in the spout is openable by operation of a valve member.

22. An applicator system according to any of claims 15 to 20, wherein a plurality of air inlets in the spout are openable by operation of a valve member.

23. An applicator system according to claim 21 or claim 22, wherein the single elongate passageway in the spout is also openable by operation of the valve member.

24. An applicator system according to claim 23, wherein the valve member comprises an annular flapper valve surrounding a central quadrolobe valve which is a push fit within the single elongate passageway in the spout.

25. An applicator system according to any of claims 3, 7, 10 or 11, or any claim when dependent on claims 3, 7, 10 or 11, wherein the elongate parting members project from a support to which the flowable composition is delivered through a housing.

26. An applicator system according to claim 25 and any of claims 15 to 24, wherein the housing has a guide tube which receives a free end of the spout when the housing is located over the spout.

27. An applicator system according to claim 25 or claim 26, wherein each of the elongate parting members is in the form of a substantially rigid tooth.

28. An applicator system according to claim 27, wherein the teeth are arranged in at least one row, with a free end of each of the teeth having at least one of the outlets.

29. An applicator system according to any of claims 25 to 28, wherein the elongate parting members and the support are removably detachable from the housing.

30. An applicator system according to claim 29, wherein the elongate parting members and the support are formed as a unit which is securable to the housing by securing means including a catch.

31. An applicator system according to claim 30, wherein the catch is resiliently deflectable and engageable with an aperture extending through the housing, the catch being releasable remotely from the elongate parting members.

32. An applicator system according to claim 31, wherein there is a further catch operable as a pivot.

33. An applicator system according to any of claims 29 to 32, wherein there is a plurality of the supports from which one is to be selected by a user, the elongate parting members of different supports being of different type.

34. An applicator system according to any of claims 25 to 33, wherein the housing is a removable screw fit with the container.

35. An applicator system according to claim 34, wherein the housing and the container are formed with lug means which snap passed one another when the housing has been fully screwed onto the container.


36. An applicator system according to any preceding claim, wherein the container is a bag-in-bottle container such that the flowable composition can be delivered at any orientation of the bag-in-bottle container.

37. An applicator system according to claim 36, wherein a valve member of unitary construction is operable to control both entry of air into the bottle and exit of flowable composition from the bag.

38. An applicator system according to any preceding claim, wherein the flowable composition is a hair and/or scalp composition.

1/6

Fig.1.



2/6






Fig.4.



3/6

Fig.5.





Fig.6.



4/6

Fig.7.






Fig.8.






5/6

Fig.9.



6/6



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/24835

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 A45D19/02 A45D24/26 B65D35/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A45D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 643 403 A (POOLE DANIEL L ET AL) 1 July 1997 see column 7, line 28 - line 29 see column 7, line 35 - line 43 see column 7, line 50 see column 7, line 56 - line 66 see column 8, line 6 - line 7 see figures 14,16-20	1-4,10, 13-19, 25,26, 29-31,33
A Y	---	6-9 11,12, 20-23, 27,28, 36,38
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 February 1999

Date of mailing of the international search report

03/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Claudel, B

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 98/24835

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GB 2 174 356 A (ALBYN OF STONEHAVEN LIMITED) 5 November 1986 see page 1; figures ----	11,12, 27,28,38
Y	US 5 615 803 A (HATAKEYAMA YOSHIHARU ET AL) 1 April 1997 see column 1, line 65 - column 2, line 37 see column 4, line 9 - line 31 see column 5, line 63 - column 6, line 31 see figures 4,7,8 ----	21-23,36
A	----	37
Y	US 5 299 877 A (BIRDEN DONALD) 5 April 1994 see column 3, line 55 - line 63 see figure 2 ----	20
A	DE 39 31 111 A (SOLTENAU RUPERT) 28 March 1991 see column 3, line 22 - column 4, line 39 see figures ----	5,27,28, 34
A	CH 118 931 A (ROBERT RUDOLF-SCHNEITTER) 16 February 1927 see claims 8-11; figure 2 ----	5-7,34
A	US 4 011 879 A (ROBERTS SHEPARD D) 15 March 1977 see column 2, line 8 - line 44 ----	5,34
A	US 5 316 403 A (MANSOUR AMIN F) 31 May 1994 see column 2, line 59 - column 3, line 36 ----	5,34
A	DE 89 02 166 U (SCHWAN-STABILO) 15 June 1989 see page 7, line 7 - line 20; figures 1,4 ----	5,34
A	US 4 781 311 A (DUNNING WALTER B ET AL) 1 November 1988 see the whole document ----	35
A	EP 0 380 251 A (ELOPAK SYSTEMS) 1 August 1990 see column 2, line 37 - line 48 -----	24

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 98/24835

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5643403	A	01-07-1997	AU 4523896 A WO 9619350 A	10-07-1996 27-06-1996
GB 2174356	A	05-11-1986	NONE	
US 5615803	A	01-04-1997	JP 8164954 A FR 2728244 A	25-06-1996 21-06-1996
US 5299877	A	05-04-1994	NONE	
DE 3931111	A	28-03-1991	NONE	
CH 118931	A		NONE	
US 4011879	A	15-03-1977	NONE	
US 5316403	A	31-05-1994	NONE	
DE 8902166	U	15-06-1989	NONE	
US 4781311	A	01-11-1988	AU 575673 B AU 4626385 A EP 0176206 A JP 61082860 A	04-08-1988 20-02-1986 02-04-1986 26-04-1986
EP 0380251	A	01-08-1990	DK 380251 T JP 2233302 A JP 2840969 B US 5052594 A	28-06-1993 14-09-1990 24-12-1998 01-10-1991